

Specifications

Rebar Cutters

MODEL	HBC-10	HBC-25	BC-25
CUTTING CAPACITY GRADE 40			
Bar Size	No. 6	No. 8	No. 8
in. (mm)	3/4 (19)	1 (25)	1 (25)
CUTTING CAPACITY GRADE 50			
Bar Size	No. 6	No. 8	No. 8
in. (mm)	3/4 (19)	1 (25)	1 (25)
CUTTING CAPACITY GRADE 60			
Bar Size	No. 5	No. 7	No. 7
in. (mm)	5/8 (16)	7/8 (22)	7/8 (22)
Max. Cutting Speed	3	4.5	9
Rated Power amps	9	12	12
Electric Motor	11.5 Volts, 60 Hz, single-phase AC		
DIMENSIONS & WEIGHT			
Length in. (mm)	15.3 (38)	18.3 (46.4)	23.8 (60.4)
Width in. (mm)	4.4 (11)	5.9 (15)	9.8 (25)
Height in. (mm)	8.8 (23)	9.4 (24)	9.5 (24)
Weight lbs. (kg)	2.7 (1.2)	4.8 (2.2)	1.29 (58)
STANDARD EQUIPMENT			
Haz. Wrenches	2	2	3
Hydraulic Oil	2	2	n/a
Carrying Box	Wood	Wood	n/a

Features and specifications are subject to change without notice.

Rebar Bender

MODEL	MB-25HD
MAXIMUM BENDING CAPACITY	
in. (mm)	
1" (25.4)	
RANGE OF BENDS	
0° to 180°	
STANDARD BENDING RADIUS	
Rebar No. in. (mm)	Radius in. (mm)
No. 3 - 3/8" (9.5)	3/4" (19)
No. 4 - 1/2" (12.7)	15/16" (24)
No. 5 - 5/8" (15.9)	1 - 1/16" (24)
No. 6 - 3/4" (19.0)	1 - 7/8" (22)
No. 7 - 7/8" (22.2)	2 - 3/16" (35)
No. 8 - 1" (25.4)	2 - 7/16" (42)
MAXIMUM BENDING SPEED	
Approximately 5 seconds for 180° angle	
MOTOR SPECIFICATIONS	
Electric Motor*	11.5V, 60Hz, Single Phase, AC
Rated Power (amps)	15
DIMENSIONS & WEIGHT	
Dimensions LxWxH	16.1(41) x 17.9 (45) x 19.5 (1.36)
Weight lbs. (kg)	300 (134)
STANDARD EQUIPMENT	
Foot Switch	
Rollers (3 steel)	
Cutters (4 steel)	
Tool Kit	
Waterproof Cover	

*International Standard Voltage and Hz Electric Motor models available upon request. Specify Voltage and Hz with order.



Rebar Cutters & Benders

Whiteman Concrete Division



Reduce labor, increase profits



HBC-10

BC-25

MB-25HD

Your Multiquip dealer is:

superiorequipmentonline.com



Atlanta - Bolso - Newark - Montreal, Canada
 Marchocha - UK - Rio de Janeiro, Brazil - Guadalajara, Mexico

MQRS24P-002 REV. (12/00)